

Vertical Light Bar is a contemporary design that is both timeless and unique in its impression. Compact without visible mounting equipment and optimised integration, Vertical Light Bar is in perfect continuity with the geometric lines of the square column. These assemblies are ideal for surroundings of contemporary architectural constructions.

Product Description

- Integrated with LED Modules.
- Polycarbonate optical lens.
- Integral power supply
- Earth connection
- Safety class I
- **CE** - Conformity mark
- **BIS** - Conformity mark
- Pole made of Mild Steel
- Pole design parameters vary depending on the type of bracket and loading factor.
- All pole sections are welded using special v groove technique by certified welders using high end MIG welding processes.
- Built-in control box with die cast aluminium service door and vandal resistant loss proof screw.
- The control gear tray is prewired with MCB, terminal connectors for loop-in / loop-out arrangement.
- The foundation bolt holes in the base plate are designed to be elongated for fine adjustments / alignment of the pole during installation.
- Base plate made of steel grade E250 & foundation bolt of grade 4.6

Product Benefits

- Quick installation and low assembly costs.
- A wide range of Pole heights and bracket options to meet various lighting requirements.
- Functionally versatile, strong and stable.
- Innovative design options to provide visual integration with the environment.
- High Brightness, LED Light source do not pose any environment risks.
- Designed for highest efficiency in terms of more lumens at reduced wattages contributing to a Greener World.
- Customised for your delight : Creating the entire product portfolio - Right from concept to completion, merging the best technology and practices in lighting.

Area of Application

Smaller Roadways, Private driveways, Residential Area Lighting, Courtyards, Public area lighting like parks & Squares.

Installation

Surface mounted with base plate and fitted on a pre formed foundation.

Available Finish

Coated with zinc rich primer and finished using environmentally stable polyurethane based paint / Pure polyester powder coated of desired colour.

- RAL 9004 Black
- RAL 7016 Anthracite grey
- Graphite grey

VERTICAL LIGHT BAR


□100 Series

Code	Wattage	Height	Mounting
12058-500-SA-00-40	1 x 40W LED	5000	F105.3
12058-500-AA-00-40	2 x 40W LED	5000	F105.3

Lighting Module Datasheet - 40W

LED Brand	LUMILEDS SMD 7070
Module voltage/current	25-50V, 750 mA
Colour Temperature	3000K / 4000K / 5700K
Colour rendering index	>70
Luminous flux(lm)	3576 / 4065 / 4049 lm
Power consumption(w)	40W
Luminaire efficacy(lm/W)	94 / 109 / 109 lm/W
Operating temperature(°C)	-15°~+50°C
Optics	Narrow Beam / Wide Beam
Ingress Protection	IP67
Impact Protection	IK08
Optical Cover	Polycarbonate
Certification	LM80 certified / RoHS / CE confirmed

Note
Luminous flux and power consumption allowance is ±10%,
CRI allowance is ±5.



12058-500-SA-00-40



12058-500-AA-00-40