

The Luna Midi Pendant is a specialized outdoor luminaire designed as an integral model with a totally weatherproof and aesthetically contoured build. It offers enhanced long-lasting protection against the ingress of dust, moisture, and insects within the optical compartment. The product is available with an asymmetrical light distribution, making it suitable for a variety of outdoor lighting applications.

MATERIAL

Body	: Pressure die cast aluminium
Impact Protection	: IK08
Ingress Protection	: IP66
Diffuser	: Clear toughened glass of 5mm thickness
Lens	: Polycarbonate optical lens
Gasket	: Silicone compression gasket
Glare Control	: Slight regress in the optical assembly for better glare control
Mounting	: Suitable for mounting to Internally threaded pipe of designation M30.

ELECTRICAL

Driver	: Standard
Power Supply	: Integral
Input Voltage	: 230-240Vac / 50-60 Hz
Surge	: 4KV / 6KV

PRODUCT CONFIGURATIONS

Wattage	: 30W / 50W
Light Distribution	: Type II / Type III / Type IV
CCT	: 3000K / 4000K / 5700K
LED Life Time	: L70 B10 1,00000 H

AREA OF APPLICATION

Street Lighting, Smaller Roadways, Private driveways, Residential Area Lighting, Public area lighting like parks & Squares.

AVAILABLE FINISH

Pure polyester powder coated
RAL 9004 Black
RAL 7016 Anthracite grey
Graphite grey





Technical Specifications

General

ID	: 22806
System Wattage	: 30W / 50W
Driver Integral	: Constant Current
Operating Voltage	: 110-300Vac
Operating Temperature	: -15°C~+50°C

Physical

Body	: Die-Cast Aluminum
Diffuser	: Clear Toughened Glass
Mounting	: Internally threaded pipe of designation : M30
Finish	: Powder coated RAL 9004 Black RAL 7016 Anthracite grey Graphite grey

Light Source

Light Source	: LUMILEDS
CRI (Ra)	: >70
LED Colour Temperature	: 3000K / 4000K / 5700K

Driver

Power Supply	: Integral
Input Voltage	: 230-240Vac
Frequency	: 50-60 Hz
Power Factor	: >0.95
THD	: <10%
Surge Protection	: 4KV / 6KV
Efficiency	: >85%

Optical Performance

Light Distribution	: Type II / Type III / Type IV
--------------------	--------------------------------

