

1		2		3		4		IF IN DOUBT ASK.		DO NOT SCALE.		5		6		7		8																																																																																											
1 of 1 : 'ON LITE SHS 521-DFD-TK : 'ON G.W.M.D										ALL DIMENSIONS ARE IN MM																																																																																																			
K - LITE STANDARD POLE FOUNDATION DETAILS																																																																																																													
<table><tr><th>Figure</th><th>Base plate (A)</th><th>No.of holes/ bolts (C)</th><th>CC (D)</th><th>Foundation bolt projection height (I)</th><th>Bolt (E)</th><th>Length (F)</th><th>RCC Height below GL / Digging depth (I)</th><th>Length of RCC layer (J)</th><th>Length of coarse sand layer (K)</th></tr><tr><td>F105.1</td><td>□200 x 12thk</td><td>4</td><td>140</td><td>75</td><td>M16</td><td>300</td><td>800</td><td>□400</td><td>□500</td></tr><tr><td>F105.2</td><td>□200 x 12thk</td><td>4</td><td>140</td><td>75</td><td>M16</td><td>500</td><td>800</td><td>□400</td><td>□500</td></tr><tr><td>F105.3</td><td>□250 x 12thk</td><td>4</td><td>180</td><td>75</td><td>M16</td><td>500</td><td>1000</td><td>□400</td><td>□500</td></tr><tr><td>F105.4</td><td>□300 x 16thk</td><td>4</td><td>215</td><td>90</td><td>M20</td><td>500</td><td>1200</td><td>□400</td><td>□500</td></tr><tr><td>F105.5</td><td>□400 x 16thk</td><td>4</td><td>300</td><td>90</td><td>M20</td><td>500</td><td>1500</td><td>□500</td><td>□600</td></tr><tr><td>F105.6</td><td>□400 x 16thk</td><td>4</td><td>300</td><td>90</td><td>M20</td><td>700</td><td>1800</td><td>□500</td><td>□600</td></tr><tr><td>F105.7</td><td>□400 x 16thk</td><td>4</td><td>300</td><td>125</td><td>M24</td><td>1000</td><td>2000</td><td>□500</td><td>□600</td></tr></table>																				Figure	Base plate (A)	No.of holes/ bolts (C)	CC (D)	Foundation bolt projection height (I)	Bolt (E)	Length (F)	RCC Height below GL / Digging depth (I)	Length of RCC layer (J)	Length of coarse sand layer (K)	F105.1	□200 x 12thk	4	140	75	M16	300	800	□400	□500	F105.2	□200 x 12thk	4	140	75	M16	500	800	□400	□500	F105.3	□250 x 12thk	4	180	75	M16	500	1000	□400	□500	F105.4	□300 x 16thk	4	215	90	M20	500	1200	□400	□500	F105.5	□400 x 16thk	4	300	90	M20	500	1500	□500	□600	F105.6	□400 x 16thk	4	300	90	M20	700	1800	□500	□600	F105.7	□400 x 16thk	4	300	125	M24	1000	2000	□500	□600										
Figure	Base plate (A)	No.of holes/ bolts (C)	CC (D)	Foundation bolt projection height (I)	Bolt (E)	Length (F)	RCC Height below GL / Digging depth (I)	Length of RCC layer (J)	Length of coarse sand layer (K)																																																																																																				
F105.1	□200 x 12thk	4	140	75	M16	300	800	□400	□500																																																																																																				
F105.2	□200 x 12thk	4	140	75	M16	500	800	□400	□500																																																																																																				
F105.3	□250 x 12thk	4	180	75	M16	500	1000	□400	□500																																																																																																				
F105.4	□300 x 16thk	4	215	90	M20	500	1200	□400	□500																																																																																																				
F105.5	□400 x 16thk	4	300	90	M20	500	1500	□500	□600																																																																																																				
F105.6	□400 x 16thk	4	300	90	M20	700	1800	□500	□600																																																																																																				
F105.7	□400 x 16thk	4	300	125	M24	1000	2000	□500	□600																																																																																																				
<table><tr><th colspan="10">K - LITE STANDARD POLE FOUNDATION DETAILS</th></tr><tr><th>Figure</th><th>Base plate (A)</th><th>No.of holes/ bolts (C)</th><th>CC (D)</th><th>Foundation bolt projection height (I)</th><th>Bolt (E)</th><th>Length (F)</th><th>RCC Height below GL / Digging depth (I)</th><th>Length of RCC layer (J)</th><th>Length of coarse sand layer (K)</th></tr><tr><td>F105.1</td><td>□200 x 12thk</td><td>4</td><td>140</td><td>75</td><td>M16</td><td>300</td><td>800</td><td>□500</td><td>□600</td></tr><tr><td>F105.2</td><td>□200 x 12thk</td><td>4</td><td>140</td><td>75</td><td>M16</td><td>500</td><td>800</td><td>□500</td><td>□600</td></tr><tr><td>F105.3</td><td>□250 x 12thk</td><td>4</td><td>180</td><td>75</td><td>M16</td><td>500</td><td>1000</td><td>□500</td><td>□600</td></tr><tr><td>F105.4</td><td>□300 x 16thk</td><td>4</td><td>215</td><td>90</td><td>M20</td><td>500</td><td>1200</td><td>□500</td><td>□600</td></tr><tr><td>F105.5</td><td>□400 x 16thk</td><td>4</td><td>300</td><td>90</td><td>M20</td><td>500</td><td>1500</td><td>□500</td><td>□600</td></tr><tr><td>F105.6</td><td>□400 x 16thk</td><td>4</td><td>300</td><td>90</td><td>M20</td><td>700</td><td>1800</td><td>□500</td><td>□600</td></tr><tr><td>F105.7</td><td>□400 x 16thk</td><td>4</td><td>300</td><td>125</td><td>M24</td><td>1000</td><td>2000</td><td>□500</td><td>□600</td></tr></table>																				K - LITE STANDARD POLE FOUNDATION DETAILS										Figure	Base plate (A)	No.of holes/ bolts (C)	CC (D)	Foundation bolt projection height (I)	Bolt (E)	Length (F)	RCC Height below GL / Digging depth (I)	Length of RCC layer (J)	Length of coarse sand layer (K)	F105.1	□200 x 12thk	4	140	75	M16	300	800	□500	□600	F105.2	□200 x 12thk	4	140	75	M16	500	800	□500	□600	F105.3	□250 x 12thk	4	180	75	M16	500	1000	□500	□600	F105.4	□300 x 16thk	4	215	90	M20	500	1200	□500	□600	F105.5	□400 x 16thk	4	300	90	M20	500	1500	□500	□600	F105.6	□400 x 16thk	4	300	90	M20	700	1800	□500	□600	F105.7	□400 x 16thk	4	300	125	M24	1000	2000	□500	□600
K - LITE STANDARD POLE FOUNDATION DETAILS																																																																																																													
Figure	Base plate (A)	No.of holes/ bolts (C)	CC (D)	Foundation bolt projection height (I)	Bolt (E)	Length (F)	RCC Height below GL / Digging depth (I)	Length of RCC layer (J)	Length of coarse sand layer (K)																																																																																																				
F105.1	□200 x 12thk	4	140	75	M16	300	800	□500	□600																																																																																																				
F105.2	□200 x 12thk	4	140	75	M16	500	800	□500	□600																																																																																																				
F105.3	□250 x 12thk	4	180	75	M16	500	1000	□500	□600																																																																																																				
F105.4	□300 x 16thk	4	215	90	M20	500	1200	□500	□600																																																																																																				
F105.5	□400 x 16thk	4	300	90	M20	500	1500	□500	□600																																																																																																				
F105.6	□400 x 16thk	4	300	90	M20	700	1800	□500	□600																																																																																																				
F105.7	□400 x 16thk	4	300	125	M24	1000	2000	□500	□600																																																																																																				
1. This is a typical foundation drawing provided for reference purposes only. K-Lite Industries Pvt. Ltd. shall not be held liable for the structural adequacy, stability, or suitability of the foundation for the specific site conditions. 2. Please consult the local structural/site engineer for the detailed foundation design. 3. Parameters considered in RCC foundation design : Load bearing capacity of soil (LBC) : 10 Mt/m² (Minimum) Grade of steel reinforcement : Fe 415 Grade of foundation bolt : 4.6 4. Height of foundation above ground level (150mm) may be revised to suit the site conditions especially considering the expected water level stagnation. 5. Template supplied is suggested to be used for locating the CC of foundation bolts. 6. 4 Nos. of foundation bolt have to be oriented (located), while casting the foundation such that the door of the electrical junction box face the required direction. 7. PVC / GI pipe for entry of supply cable and the materials required for foundation are not scope of our supply. 8. Cable entry hole as per base pipe size.																																																																																																													
Section: A - A																																																																																																													
<table><tr><th>REV. No.</th><th>REVISION DETAILS</th><th>DATE</th><th>REVISED</th><th>CHECKED</th><th>APPROVED</th></tr><tr><td>1</td><td></td><td></td><td></td><td></td><td></td></tr></table>																				REV. No.	REVISION DETAILS	DATE	REVISED	CHECKED	APPROVED	1																																																																																			
REV. No.	REVISION DETAILS	DATE	REVISED	CHECKED	APPROVED																																																																																																								
1																																																																																																													
<table><tr><td colspan="2">DRAWN R.SATHISH</td><td>CHECKED</td><td>APPROVED</td><td>DATE 19-09-2026</td><td>SCALE 1:40</td></tr><tr><td colspan="2">K-LITE INDUSTRIES PRIVATE LIMITED CHENNAI-600 058</td><td colspan="4">Z:\K - LITE\006.FOUNDATION DETAIL\SKL-DFD-125 (F105)\KL-DFD-125_REV 00 (K-P-105).dwg</td></tr><tr><td colspan="2">DRG. No. KL-DFD-125</td><td>REV. 00</td><td colspan="3">SHEET 1 of 1</td></tr></table>																				DRAWN R.SATHISH		CHECKED	APPROVED	DATE 19-09-2026	SCALE 1:40	K-LITE INDUSTRIES PRIVATE LIMITED CHENNAI-600 058		Z:\K - LITE\006.FOUNDATION DETAIL\SKL-DFD-125 (F105)\KL-DFD-125_REV 00 (K-P-105).dwg				DRG. No. KL-DFD-125		REV. 00	SHEET 1 of 1																																																																										
DRAWN R.SATHISH		CHECKED	APPROVED	DATE 19-09-2026	SCALE 1:40																																																																																																								
K-LITE INDUSTRIES PRIVATE LIMITED CHENNAI-600 058		Z:\K - LITE\006.FOUNDATION DETAIL\SKL-DFD-125 (F105)\KL-DFD-125_REV 00 (K-P-105).dwg																																																																																																											
DRG. No. KL-DFD-125		REV. 00	SHEET 1 of 1																																																																																																										