K-LITE

# Dynasty Midi



RAMNIWAS BAGH, JAIPUR



## Technical Specifications

### General

| | |
|---|---|
| ID | : 21807 |
| System Wattage | : 30W |
| Driver Integral | : Constant Current |
| Operating Voltage | : 100-277Vac |
| Operating Temperature | : -15°C~+50°C |

### Physical

| | |
|---|---|
| Body | : Die Cast Aluminium top cover |
| Diffuser | : Translucent / Textured Acrylic |
| Mounting | : Suitable for Mounting on Ø50mm OD Pipe |
| Finish | : Powder coated<br>RAL 9004 Black<br>RAL 7016 Anthracite grey<br>Graphite grey |

### Light Source


| | |
|---|---|
| Light Source | : LUMILEDS |
| CRI (Ra) | : >70 |
| LED Colour Temperature | : 2700K / 3000K / 4000K 5700K |

### Driver

| | |
|---|---|
| Power Supply | : Integral |
| Input Voltage | : 230-240Vac |
| Frequency | : 50-60Hz |
| Power Factor | : >0.95 |
| THD | : <10% |
| Surge Protection | : 4KV |
| Efficiency | : >85% |

### Optical Performance

| | |
|---|---|
| Light Distribution | : Symmetrical |




IP65

## Diffuser Options



C1 - Textured Diffuser



C2 - Translucent Diffuser

**Note :** It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at **www.klite.in**


K-LITE

# Dynasty Midi



CITY PARK, JAIPUR






## Technical Specifications

### General

| | |
|---|---|
| ID | : 21807 |
| System Wattage | : 50W |
| Driver Integral | : Constant Current |
| Operating Voltage | : 100-277Vac |
| Operating Temperature | : -15°C~+50°C |

### Physical

| | |
|---|---|
| Body | : Die Cast Aluminium top cover |
| Diffuser | : Textured / Translucent Acrylic |
| Mounting | : Suitable for Mounting on Ø50mm OD Pipe |
| Finish | : Powder coated<br>RAL 9004 Black<br>RAL 7016 Anthracite grey<br>Graphite grey |

### Light Source

| | |
|---|---|
| Light Source | : LUMILEDS |
| CRI (Ra) | : >70 |
| LED Colour Temperature | : 2700K / 3000K / 4000K 5700K |

### Driver

| | |
|---|---|
| Power Supply | : Integral |
| Input Voltage | : 230-240Vac |
| Frequency | : 50-60Hz |
| Power Factor | : >0.95 |
| THD | : <10% |
| Surge Protection | : 6KV |
| Efficiency | : >88% |

### Optical Performance

| | |
|---|---|
| Light Distribution | : Symmetrical |

IP65

## Diffuser Options



C1 - Textured Diffuser



C2 - Translucent Diffuser

**Note :** It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at **www.klite.in**

K-LITE

# Dynasty Midi





MAA SAMALESWARI TEMPLE, ODISHA

## Technical Specifications

### General

| | |
|---|---|
| ID | : 21807 |
| System Wattage | : 50W Asy |
| Driver Integral | : Constant Current |
| Operating Voltage | : 100-277Vac |
| Operating Temperature | : -15°C~+50°C |

### Physical

| | |
|---|---|
| Body | : Die Cast Aluminium top cover |
| Diffuser | : Polycarbonate Optical Lens |
| Mounting | : Suitable for Mounting on Ø50mm OD Pipe |
| Finish | : Powder coated<br>RAL 9004 Black<br>RAL 7016 Anthracite grey<br>Graphite grey |

### Light Source


| | |
|---|---|
| Light Source | : LUMILEDS |
| CRI (Ra) | : >70 |
| LED Colour Temperature | : 2700K / 3000K / 4000K 5700K |

### Driver

| | |
|---|---|
| Power Supply | : Integral |
| Input Voltage | : 230-240Vac |
| Frequency | : 50-60Hz |
| Power Factor | : >0.95 |
| THD | : <10% |
| Surge Protection | : 6KV |
| Efficiency | : >88% |

### Optical Performance

| | |
|---|---|
| Light Distribution | : Type III |




IP65

## Diffuser Options



C0 - Without Diffuser

**Note :** It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at **www.klite.in**