Technical data.

PARAMETER	CANVAS MINI	CANVAS MIDI	CANVAS
Article number	KL-22555	KL-22556	KL-22557
System power	100W	200W	300W
Luminous flux (lm)	>16500 lm	>32200 lm	>48400 lm
Luminaire efficacy	> 160 lm/W	> 160 lm/W	> 160 lm/W
Dimensions L × B × H	318 x 103 x 235 mm	370 x 103 x 280 mm	422 x 109 x 336 mm
Weight	3.6 Kg	5 Kg	7.5 Kg
Colour temperature	2700K · 3000K · 4000K · 5700K		
Colour rendering	Ra > 70		
Optical Beam Angle	30° · 60° · 90° · 150° · Asymmetrical		
Input Voltage	90-305 Vac · 50/60 Hz		
Electrical Safety Class	Class I		
Power factor	>0.98		
THD	<10%		
Dimmable Option	DALI-2 · 0-10V (on request)		
Overvoltage protection	6 KV · External 10KV / 20KV SPD on request		
Ambient temperature	−15°C to +50°C		
Ingress Protection	IP66		
Impact Protection	IK08		
Optical closure	Clear toughened glass, 5mm thickness		
Housing	Pressure die-cast aluminium		
Finishes	Polyester powder coat, RAL 9004 Black · Graphite grey		
Mounting	Stainless steel stirrup bracket with smooth 360° rotation in both clockwise and anti-clockwise directions.		
Service life L70B10	100000Hr		
Warranty	5 years		
Conformity	BIS · IES LM-79 · LM-80 / TM-21 [1]		
Accessories	Anti-glare visor · external SPD (on request)		

[1] Type-test programme in completion at the K-Lite photometric laboratory, Chennai (goniophotometer, LM-79 / LM-80 protocols). Certified values are published in the technical supplement and at klite.in. Luminous flux and power consumption tolerance ±10%.
Note : All parameters may vary by ±10%.