K-LITE

# Kayal Mini





## Technical Specifications

### General

| | |
|---|---|
| ID | : 24370 |
| System Wattage | : 30W |
| Driver Integral | : Constant Current |
| Operating Voltage | : 100-277Vac |
| Operating Temperature | : -15°C~+50°C |

### Physical

| | |
|---|---|
| Body | : Extruded Aluminium |
| Diffuser | : Clear Toughened Glass |
| Mounting | : Wall - Surface |
| Finish | : Powder coated<br>RAL 9004 Black<br>RAL 7016 Anthracite grey<br>Graphite grey |

### Light Source


| | |
|---|---|
| Light Source | : LUMILEDS |
| CRI (Ra) | : >70 |
| LED Colour Temperature | : 2700K / 3000K / 4000K<br>5700K |

### Driver


| | |
|---|---|
| Power Supply | : Integral |
| Input Voltage | : 230-240Vac |
| Frequency | : 50-60Hz |
| Power Factor | : >0.95 |
| THD | : <10% |
| Surge Protection | : 4KV |
| Efficiency | : >85% |

### Optical Performance

| | |
|---|---|
| Light Distribution | : Type II, Type III, Type IV |




IP65 IK08




**Note :** It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at **www.klite.in**