K-LiTE Gema

This elegant and efficient lantern, featuring a clear diffuser, offers a unique and comfortable lighting experience with symmetrical light distribution. Its aesthetically designed, sturdy construction guarantees long-lasting performance, even in the harshest weather conditions.

Product Description

- The luminaire made of spun aluminium top cover and extruded aluminium pipe along with pressure die cast aluminium base.
- · Non yellowing UV stabilised clear acrylic diffuser.
- Brite aluminium reflector is profiled for improved illumination efficiency.
- · Luminaire integrated with 30W LED.
- Die cast aluminium base for effective corrosion resistance.
- Suitable for mounting on 60mm OD pipe.
- · Cable entries for through-wiring of mains supply cable.
- · Integral constant current power supply
- CRI (Ra): ≥80
- Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply.
- Ordering guide: KL-24520-CCT (Colour Temperature)
- · Available CCT: 2700K, 3000K, 4000K, 5700K



Product Benefits

- · Elegant, Robust design
- · Environmental friendly, moisture proof, insect free.
- The diffuser contributes to the creation of ambiance and to visual comfort by reducing glare.
- · Low maintenance cost.

Area of Application

Illuminating parks, Gardens, commercial complex, Residential roadways, Walkways, Streetscapes & office complex.

Available Finish

Pure polyester powder coated RAL 9004 Black RAL 9007 Grey aluminium RAL 7016 Anthracite grey Graphite grey



K-LiTE Gema





OPEN SOURCE

Technical Specifications General

ID : 24520 System Wattage : 30W LED Driver Integral : Constant Current Operating Voltage : 100-277Vac Operating Temperature :-15°C~+50°C

Physical

Body : Spun aluminium top cover & Extruded aluminium Diffuser : Clear acrylic : Suitable for Mounting Mounting on Ø60mm OD Pipe Finish : Powder coated RAL 9004 Black

RAL 9007 Grey aluminium RAL 7016 Anthracite grey

Graphite grey

Light Source

Light Source : NICHIA CŘI (Ra) :≥80

: 2700K / 3000K / 4000K LED Colour Temperature

5700K

Driver

Power Supply : Integral Input Voltage : 230-240Vac Frequency : 50-60Hz Power Factor :>0.95 THD :<10% Surge Protection : 4KV Efficiency :>88%

Optical Performance

Light Distribution : Symmetrical











