



Technical Specifications

General

| | |
|-----------------------|--------------------|
| ID | : 24419 |
| System Wattage | : 60W LED |
| Driver Integral | : Constant Current |
| Operating Voltage | : 100-277Vac |
| Operating Temperature | : -15°C~+50°C |

Physical

| | |
|----------|---|
| Body | : Extruded Aluminium |
| Diffuser | : Polycarbonate Optical Lens |
| Mounting | : Suitable for mounting on Ø76mm, Ø88.9mm, □72mm, □91mm Pipe |
| Finish | : Powder coated RAL 9004 Black RAL 9007 Grey aluminium RAL 7016 Anthracite grey Graphite grey |

Light Source

| | |
|------------------------|------------------------------------|
| Light Source | : NICHIA |
| CRI (Ra) | : >80 |
| LED Colour Temperature | : 2700K / 3000K / 4000K / 5700K |

Driver

| | |
|------------------|--------------|
| Power Supply | : Integral |
| Input Voltage | : 230-240Vac |
| Frequency | : 50-60 Hz |
| Power Factor | : >0.9 |
| THD | : <10% |
| Surge Protection | : 4KV |
| Efficiency | : >85% |

Optical Performance

| | |
|--------------------|------------|
| Light Distribution | : Type III |
|--------------------|------------|

