



ALIPORE JAIL MUSEUM, KOLKATA



**Technical Specifications**

**General**

ID : 6951/6952/6953  
 System Wattage : 9W LED  
 Driver Integral : Constant Current  
 Operating Voltage : 100-277Vac  
 Operating Temperature : -15°C~+50°C

**Light Source**

Light Source : NICHIA  
 CRI (Ra) : ≥80  
 LED Colour Temperature : 2700K / 3000K / 4000K / 5700K

**Physical**



Body : Extruded Aluminium Tube & Die Cast Aluminium  
 Diffuser : Translucent Polycarbonate  
 Gasket : Silicone  
 Mounting : Surface  
 Finish : Powder coated  
 RAL 9004 Signal black  
 RAL 9007 Grey aluminium  
 RAL 7016 Anthracite grey  
 Graphite grey

**Driver**

Power Supply : Integral  
 Input Voltage : 230-240Vac  
 Frequency : 50-60 Hz  
 Power Factor : ≥0.95  
 THD : <10%  
 Surge Protection : 2.5KV  
 Efficiency : >80%

**Optical Performance**

Light Distribution : Symmetrical



**Note :** It is our constant endeavor to upgrade the performance of our products. For the latest technical information, IES files and product updates please refer to the website at [www.klite.in](http://www.klite.in)